

4

3

2

1

**AIR SHAFT ASSEMBLIES**  
 820-02-534-KIT: Air Shaft Assy, 2019, 36, 180mm, FLOAT LC NA 2, 1.287 Bore, TO Hat  
 820-02-535-KIT: Air Shaft Assy, 2019, 36, 170mm, FLOAT LC NA 2, 1.287 Bore, TO Hat  
 820-02-536-KIT: Air Shaft Assy, 2019, 36, 160mm, FLOAT LC NA 2, 1.287 Bore, TO Hat  
 820-02-537-KIT: Air Shaft Assy, 2019, 36, 150mm, FLOAT LC NA 2, 1.287 Bore, TO Hat  
 820-02-538-KIT: Air Shaft Assy, 2019, 36, 140mm, FLOAT LC NA 2, 1.287 Bore, TO Hat  
 820-02-539-KIT: Air Shaft Assy, 2019, 36 831, 100mm, FLOAT LC NA 2, 1.287 Bore, TO Hat

241-00-005  
 Fastener, Custom: Nut, Bottom, R\_RL\_RLC

241-01-002  
 Fastener, Custom: Crush Washer, Plastic, R\_RL\_RLC

TORQUE:  
 50±5 IN. LB.  
 (INTO FORK CHASSIS)

IMPORTANT:  
 INSPECT 100% THAT RETAINING RING  
 IS FULLY INSTALLED INTO GROOVE FULL 360°

038-00-118  
 Retaining Ring: Internal, Smalley HHM-34-S02, Hoopster, 302 SS

029-03-008  
 O-Ring (-008) [.070 C.S. X .176 ID]

820-05-419-KIT  
 Topcap Assy, 2018 FLOAT LC NA2, 36, Black

APPLY GREASE AROUND PISTON, ON AIR SHAFT,  
 BETWEEN BUMPER AND NEG PLATE, AND A THIN LAYER ON ENTIRE  
 LENGTH OF PISTON BORE OF UPPER TUBE ID.

GREASE:  
 THIN LAYER  
 OF SLICK HONEY

TORQUE:  
 220±5 IN. LB.  
 (INTO FORK CHASSIS)

234-04-736  
 Volume Spacer, FLOAT NA 2, 36

234-04-550  
 (T) Spring Hardware: 2014 36 FLOAT Air Topcap, Al, Blue Ano

SECTION A-A

**FOX** **FOX Factory, Inc.** Ph 831-768-1100  
 130 Hangar Way, Watsonville, CA 95076 USA Fax 831-768-9312

TITLE **2019 36 FLOAT NA2**  
**Air Spring Assemblies**

SIZE DWG. NO. **C**  
 PLOT SCALE | .00:1 | SHEET | OF |

- PROPRIETARY -  
 THIS DOCUMENT CONTAINS CONFIDENTIAL, PROPRIETARY INFORMATION  
 THAT IS FOX PROPERTY. DO NOT DISCLOSE TO OR DUPLICATE  
 FOR OTHERS EXCEPT AS AUTHORIZED BY FOX.