

REFERENCE ONLY
(FOR INSTALLATION
INTO FORK)

TORQUE:
110 ± 5
IN-LBS

210-03-120
Knob, Rebound, 2011 36_40

TORQUE:
5.0 ± 1.0 IN-LB

LOCTITE:
BLUE 242
ONE DROP

018-01-004-A
Fastener, Standard: Screw [#8-32 X 0.250 TLG]

241-00-011
Fastener, Custom: Nut, Bottom, R

820-05-335-KIT
2016 FIT4 Bottom Stud Interface Parts 34

241-01-011
Fastener, Custom: Crush Washer, Plastic, 13mm

REFERENCE ONLY
(FOR INSTALLATION
INTO FORK)

TORQUE:
220 ± 5 IN-LB

Seals: U-Cup, Shore 70A, 2013 Fit-CTD and CTD-ADJ

210-22-923
Compression Adjust Knob, F-S, FIT4

TORQUE:
11 ± 3 IN-LB

036-01-043

SEE DETAIL A FOR PARTS

GREASE:
THIN LAYER
BLUE MARINE

210-22-922
Lockout Knob, F-S, FIT4

019-01-095
Fastener, Standard (Metric): Screw [M3 X 6mm] SHCS, Patchlock

820-05-330-KIT
2016 FIT4 TopCap Interface Parts F-5

010-01-004-A
BALL DIA .078

Retaining Ring: External, 8.5mm Shaft, 302SST

Plate, Detent Spring Retainer, 2013 CTD Performance

234-04-779

Spring: Detent [L.180 TLG X .090 OD X 100 lb/in] SS, LHW

GREASE:
THIN LAYER OF
BLUE MARINE ON BALL

DETAIL A
SCALE 4.000

SEE DETAIL A

FOX Factory, Inc.
130 Hangar Way, Watsonville, CA 95076 USA
Ph 831-768-1100 Fax 831-768-9312

TITLE
**2020 34 ALL Non-SC, 160 Max,
FIT4 F-S, 3 Pos Adj Cart Assy Complete**

SIZE DWG. NO.
D | 820-18-222-KIT

PLOT SCALE 1.00:1 SHEET 1 OF 1

PROPRIETARY
THIS DOCUMENT CONTAINS CONFIDENTIAL, PROPRIETARY INFORMATION
THAT IS FOR PROPERTY. DO NOT DISCLOSE TO OR DUPLICATE
FOR OTHERS EXCEPT AS AUTHORIZED BY FOX.