


4

3

2

1



SECTION A-A

! IMPORTANT:
ORIENT GAP IN PIN TOWARDS
NEG PLATE ±15°

Base Stud: Float, 0.305-48 Thread

TORQUE:
50±5 IN LBS

Seals: O-Ring [6.0mm ID x 1.5mm CS] Metric, N-70, Static

Topout Bumper, 2021 38

LOCTITE:
1-2 DROPS
RED 263

820-02-593-KIT
Neg Plate Subassembly, 2022 FLOAT LC NA 2, 34 SC, 1.222 Bore

GREASE:
THIN LAYER
SLICK HONEY

Seals: O-Ring [8.0MM ID x 1.0MM CS] Metric, N-70, Static

O-RING

PISTON

AIR SHAFT

Pin: Spring [Ø 0.188 X 0.875 TLG] Spring Steel, Zinc

FOX **FOX Factory, Inc.** Ph 831-768-1100
130 Hangar Way, Watsonville, CA 95076 USA Fax 831-768-9312

TITLE
Air Shaft Assemblies 2022
34 SC 120 MAX FLOAT NA2

SIZE DWG. NO.

C

PLOT SCALE 1:1

SHEET 1 OF 1

- PROPRIETARY -
THIS DOCUMENT CONTAINS CONFIDENTIAL, PROPRIETARY INFORMATION
THAT IS FOX PROPERTY. DO NOT DISCLOSE TO OR DUPLICATE
FOR OTHERS EXCEPT AS AUTHORIZED BY FOX.

4

3

2

ProE ASSEM