

4

3

2

1

820-05-623-KIT
2020 Grip 34, 36 & 38 P-S Topcap Interface Parts

TORQUE:
4±1 in-lb

Spring: Wave, 4 Turns, [.562 Bpre, .375 Shaft, .260 Height, 37.0 lb/in] SS

Damping Adj Part: Detent, Molded, Grip

Damping Adj Part: Detent, Molded, Grip

Seals: U-Cip, Shore 70A, 2013 CTD-ADJ, Remote O/C-CTD

GREASE:
THIN LAYER
OF SLICK HONEY

GREASE:
LIBERALLY WITH
SLICK HONEY

NOTE ORIENTAION

ENGAGE 2X FEATURES

SECTION A-A
SCALE 2.500

820-05-518-KIT
2019 36 Grip Bottom Stud Interface Parts

241-01-011
Fastener, Custom: Crush Washer, Plastic, 13mm

241-00-022
Fastener, Custom: Nut, Bottom, 011

REBOUND KNOB

TORQUE:
5.0±0.5 IN.LB.

LOCTITE:
BLUE 242 OR 243
ONE DROP

TORQUE:
150±7
(IN-LB)

SCREW

REFERENCE ONLY
(FOR INSTALLATION
INTO FORK)

FOX **FOX Factory, Inc.** Ph 831-768-1100
130 Hangar Way, Watsonville, CA 95076 USA Fax 831-768-9312

TITLE
2025 36 27.5 & 29 180 MAX,
P-S Grip Cart Assy Complete

SIZE DWG. NO.
C 820-18-554-KIT

PLOT SCALE 0.75:1 SHEET 1 OF 2

- PROPRIETARY -
THIS DOCUMENT CONTAINS CONFIDENTIAL, PROPRIETARY INFORMATION
THAT IS FOX PROPERTY. DO NOT DISCLOSE TO OR DUPLICATE
FOR OTHERS EXCEPT AS AUTHORIZED BY FOX.

4

3

2

1

ProE ASSEM