

4

3

2

1

D

D

C

C

B

B

A

A

234-44-260
Air Knob, 2022 Fox E-SUV (34)

Seals: 2020 Marzocchi Z2 Air
Knob, Red NBR 70

820-05-420-KIT
Topcap Assy, 2018 FLOAT LC NA2, 34,
SPD-PED-ELEC, Black

234-04-735
Volume Spacer, FLOAT, 2018 32 Rhythm

TORQUE:
220±5 IN-LBF
(INTO FORK CHASSIS)

Fastener, Standard(Metric) : Bolt [M8
X1.25P X16mm] Socket Button Head
Cap/Black, Oxide Alloy Steel / Grade 8.8

TORQUE:
50±5 IN-LBF
(INTO FORK CHASSIS)

Fastener, Custom: Crush
Washer, Direct Mount, [.307 ID
X .472 OD X .039 TH], Plastic

038-00-091
Retaining Ring: Internal, Smalley EH-29-S02, 302 SS

IMPORTANT:
INSPECT 100% THAT RETAINING RING
IS FULLY INSTALLED INTO GROOVE FULL 360°

AIR SHAFT ASSEMBLY

GREASE

- PROPRIETARY -
THIS DOCUMENT CONTAINS CONFIDENTIAL, PROPRIETARY INFORMATION
THAT IS FOX PROPERTY. DO NOT DISCLOSE TO OR DUPLICATE
FOR OTHERS EXCEPT AS AUTHORIZED BY FOX.

FOX **FOX Factory, Inc.** Ph 831-768-1100
 130 Hangar Way, Watsonville, CA 95076 USA Fax 831-768-9312

TITLE **Air Spring Assys, DMAS, 2025
AWL 34 E-Opt, 1.110 Bore**

SIZE DWG. NO. **C**

PLOT SCALE 1, 3: 1 | SHEET 1 OF 1