

4

3

2

1

820-05-623-KIT  
2020 Grip 34, 36 & 38 P-S Topcap Interface Parts

Spring: Wave, 4 Turns, [1.562 Bpre, .375 Shaft, .260 Height, 37.0 lb/in] SS

Damping Adj Part: Detent, Molded, Grip

Damping Adj Part: Detent, Molded, Grip

Seals: U-Cip, Shore 70A, 2013 CTD-ADJ, Remote O/C-CTD

TORQUE:  
4±1 in-lb

GREASE:  
THIN LAYER  
OF SLICK HONEY

2025 34, 160 MAX, Grip Cart Assy

GREASE:  
LIBERALLY WITH  
SLICK HONEY

ENGAGE 2X FEATURES

SECTION A-A  
SCALE 2.500

820-05-328-KIT  
2017 34 27.5 and 29in Grip Bottom Stud Interface Parts

241-01-011  
Fastener, Custom: Crush Washer, Plastic, 13mm

241-00-011  
Fastener, Custom: Nut, Bottom, R

REBOUND KNOB

TORQUE:  
5.0±0.5 IN.LB.

LOCTITE:  
BLUE 242 OR 243  
ONE DROP

TORQUE:  
150±7  
(IN-LB)

SCREW

REFERENCE ONLY  
(FOR INSTALLATION  
INTO FORK)

**FOX** **FOX Factory, Inc.** Ph 831-768-1100  
130 Hangar Way, Watsonville, CA 95076 USA Fax 831-768-9312

TITLE  
2025 34 27.5 & 29 130-160,  
Grip Cart Assy Complete

SIZE DWG. NO.  
**C** 820-18-555-KIT

PLOT SCALE 0.75:1 SHEET 1 OF 2

- PROPRIETARY -  
THIS DOCUMENT CONTAINS CONFIDENTIAL, PROPRIETARY INFORMATION  
THAT IS FOX PROPERTY. DO NOT DISCLOSE TO OR DUPLICATE  
FOR OTHERS EXCEPT AS AUTHORIZED BY FOX.

ProE ASSEM