

4

3

2

1

820-05-696-KIT
2022 32 TC Grip Topcap Interface Parts P-S

TORQUE:
4±1 in-lb

Spring: Wave, 4 Turns, [1.562 Bpre, .375 Shaft, .260 Height, 37.0 lb/in] SS

Damping Adj Part: Detent, Molded, Grip

Damping Adj Part: Detent, Molded, Grip

Seals: U-Cip, Shore 70A, 2013 CTD-ADJ, Remote O/C-CTD

GREASE:
THIN LAYER
OF SLICK HONEY

GREASE:
LIBERALLY WITH
SLICK HONEY

ENGAGE 2X FEATURES

SECTION A-A
SCALE 2.500

820-05-697-KIT
2022 32 TC GRIP Bottom Stud Interface Parts

CRUSH WASHER

BOTTOM NUT

Rebound Knob

TORQUE:
5.0±0.5 IN.LB.

LOCTITE:
BLUE 242 OR 243
ONE DROP

TORQUE:
50±5
IN-LB

SCREW

REFERENCE ONLY
(FOR INSTALLATION
INTO FORK)

FOX **FOX Factory, Inc.** Ph 831-768-1100
130 Hangar Way, Watsonville, CA 95076 USA Fax 831-768-9312

TITLE
2025 32 TC 50mm MAX GRIP
Black Ano Cart Assy Complete

SIZE DWG. NO. **820-18-573-KIT**

PLOT SCALE 0.75:1 SHEET 1 OF 2

- PROPRIETARY -
THIS DOCUMENT CONTAINS CONFIDENTIAL, PROPRIETARY INFORMATION
THAT IS FOX PROPERTY. DO NOT DISCLOSE TO OR DUPLICATE
FOR OTHERS EXCEPT AS AUTHORIZED BY FOX.

4

3

2

1

ProE ASSEM