

820-05-460-KIT
2018 Grip P-S 32 Topcap Interface Parts

TORQUE:
4±1 in-lb

Spring: Wave, 4 Turns, [1.562 Bpre, .375 Shaft, .260 Height, 37.0 lb/in] SS

Damping Adj Part: Detent, Molded, Grip

Damping Adj Part: Detent, Molded, Grip

Seals: U-Cip, Shore 70A, 2013 CTD-ADJ, Remote O/C-CTD

GREASE:
THIN LAYER
OF SLICK HONEY

GREASE:
LIBERALLY WITH
SLICK HONEY

NOTE ORIENTAION

ENGAGE 2X FEATURES

SECTION A-A
SCALE 2.500

241-01-002-C
Fastener, Custom: Crush Washer, Plastic, R_RL_RLC

241-00-005
Fastener, Custom: Nut, Bottom, R_RL_RLC

Seals: O-Ring [10.0MM ID x 2.0MM CS] Metric, N-70, Static

820-05-228-KIT
2017 FIT4 Bottom Stud Interface Parts, 32, SC, 29in Fork

REBOUND KNOB

TORQUE:
50±5
(IN-LB)

LOCTITE:
BLUE 242 OR 243
ONE DROP

TORQUE:
5.0±0.5 IN.LB.

REFERENCE ONLY
(FOR INSTALLATION
INTO FORK)

IMPORTANT:
INSTALL O-RING IN THIS LOCATION

FOX **FOX Factory, Inc.** Ph 831-768-1100
130 Hangar Way, Watsonville, CA 95076 USA Fax 831-768-9312

TITLE
**2025 32 29in SC 80-100,
Grip Cart Assy Complete**

SIZE DWG. NO.
C 820-18-556-KIT

PLOT SCALE 0.75:1 SHEET 1 OF 2

- PROPRIETARY -
THIS DOCUMENT CONTAINS CONFIDENTIAL, PROPRIETARY INFORMATION
THAT IS FOX PROPERTY. DO NOT DISCLOSE TO OR DUPLICATE
FOR OTHERS EXCEPT AS AUTHORIZED BY FOX.