



SCALE 1:1

SHOCK SUBASSEMBLY
SHOWN FOR REFERENCE ONLY

NOTE:
CONTROLLER MAY BE INSTALLED
BEFORE OR AFTER AIR SLEEVE INSTALL

IMPORTANT:
VERIFY EYELET SEALING SURFACE IS FREE
OF ANY DEBRIS, NICKS, OR DAMAGE

LOCTITE:
BLUE 243
1 DROP EACH

IMPORTANT:
CONNECT CONTROLLER TO SOLENOID
AND PLACE WIRES PER WORK INSTRUCTIONS

218-01-080
LIVE Neo Shock Controller Housing Gasket

GREASE:
CLUMP LEVEL
OF SLICK HONEY

IMPORTANT:
ENSURE GASKET IS PROPERLY
SEATED IN CONTROLLER

CONTROLLER ASSEMBLY

(241-02-186)

TORQUE:
4±0.5 IN-LBF

241-02-186
Fastener (Metric): Screw [M3 X 8mm] Button Head, Black

NOTE:
LONG SCREW THIS LOCATION ONLY

241-02-187
Fastener (Metric): Screw [M3 X 16mm] Button Head, Black

FOX FOX Factory, Inc. Ph 831-768-1100
130 Hangar Way, Watsonville, CA 95076 USA Fax 831-768-9312

TITLE
Assy Dwg: Controller Sub Assy,
2024 FLOAT X Live Valve Neo, Shock

SIZE DWG. NO. 808-17-530-KIT

PLOT SCALE 2:1 SHEET 1 OF 1

PROPRIETARY
THIS DOCUMENT CONTAINS CONFIDENTIAL, PROPRIETARY INFORMATION
THAT IS FOR PROPERTY. DO NOT DISCLOSE TO OR DUPLICATE
FOR OTHERS EXCEPT AS AUTHORIZED BY FOX.