



Seals: U-Cup, Shore 70A, 2013 Fit-CTD and CTD-ADJ

036-01-043

210-22-923  
Compression Adjust Knob, F-S, FIT4

TORQUE: 11±3 IN-LB

TORQUE: 220±5 IN-LB

GREASE: THIN LAYER BLUE MARINE

SEE DETAIL A FOR PARTS

210-22-922  
LOCKOUT KNOB

019-01-095 [5]  
Fastener, Standard (Metric): Screw [M3 X 6mm] SHCS, Patchlock

820-05-330-KIT  
TOPCAP INTERFACE PARTS

TORQUE: 150±5 IN-LB

210-03-120  
REBOUND KNOB

TORQUE: 5.0±1.0 IN-LB

LOCTITE: BLUE 242 ONE DROP

018-01-004-A  
Fastener, Standard: Screw [#8-32 X 0.250 TLG]

241-00-022  
BOTTOM NUT

820-03-377-KIT  
BASE STUD INTERFACE PARTS

241-01-011  
CRUSH WASHER

010-01-004-A  
BALL DIA .078

038-00-136  
Retaining Ring: External, 8.5mm Shaft, 302SST

234-04-779  
Plate, Detent Spring Retainer, 2013 CTD Performance

039-00-246  
Spring: Detent [L.180 TLG X .090 OD X 100 lb/in] SS, LHW

GREASE: THIN LAYER OF BLUE MARINE ON BALL

DETAIL A  
SCALE 4.000

[5] DO NOT TIGHTEN FASTENER AGAINST COMPRESSION ADJUSTER HARD STOP, USE TOOL TO PREVENT KNOB FROM TURNING

PROPRIETARY - THIS DOCUMENT CONTAINS CONFIDENTIAL, PROPRIETARY INFORMATION THAT IS FOR PROPERTY. DO NOT DISCLOSE TO OR DUPLICATE FOR OTHERS EXCEPT AS AUTHORIZED BY FOX.

**FOX Factory, Inc.**  
130 Hangar Way, Watsonville, CA 95076 USA  
Ph 831-768-1100 Fax 831-768-9312

TITLE  
**2016 Factory Series  
FIT4 Cart Assy Complete**

SIZE DWG. NO. 820-08-671-KIT  
PLOT SCALE 1.00:1 SHEET 1 OF 1