

Fastener, Custom: Air Shaft, 2014 32 26in, 27.5in, & 29in 80-150mm Evolution Series

Seals:O-Ring [(-009) .070 C.S. X 0.208 ID] Standard, N-70, Static

Washer [M5, 5.3mm ID X 10mm OD X 1mm Thk], Zinc Plated

RETAINING RING: INTERNAL, SMALLEY EH-29-S02, 302SS

Spring Hardware: Neg Plate, 2014 32mm 26in/27.5in 130-150 and 29in 110-130

234-04-439

029-03-009-A

019-01-097

038-00-091

241-02-081

TORQUE: 50±5 IN LB

OIL: 30cc GREEN 10WT OIL IN TO LOWER LEG

IMPORTANT: VERIFY THAT RETAINING RING IS FULLY ENGAGED IN UPERTUBE SNAP-RING GROOVE

234-04-444 Spacer: 10mm Travel Adjust, 2014 32 mm 26in, 27.5in, and 29in

036-01-011 U-CUP

TORQUE: 220±5 IN LB

820-02-240-KIT 2014 32 26in 80-150 and 29in 80-130 Air Shaft Assembly

036-01-060 SCRAPER

OIL: 5cc FLOAT FLUID 025-03-001-B

820-05-254 -KIT 2014 32 26in and 27.5in 80-150 Topcap Assembly

029-03-008 Seals:O-Ring [(-008) .070 C.S. X .176 ID] Standard, N-70, Static

234-04-540 (T) Spring Hardware: 2014 32 FLOAT Air Topcap, Al, Blue Ano

DESCRIPTION	234-04-444 SPACER QTY
2014 32 26IN AND 27.5IN FLOAT 150	0
2014 32 26IN AND 27.5IN FLOAT 140	1
2014 32 26IN AND 27.5IN FLOAT 130	2

FOX FOX Factory, Inc. 130 Hangar Way, Watsonville, CA 95076 USA Ph 831-768-1100 Fax 831-768-9312

TITLE Air Spring Assy E-S 2014 32 26in and 27.5in 130-150

SIZE DWG. NO. C

PLOT SCALE 1:1

SHEET 1 OF 1

PROPRIETARY - THIS DOCUMENT CONTAINS CONFIDENTIAL, PROPRIETARY INFORMATION THAT IS FOX PROPERTY. DO NOT DISCLOSE TO OR DUPLICATE FOR OTHERS EXCEPT AS AUTHORIZED BY FOX.