

4

3

2

1

D

D

C

C

B

B

A

A

820-03-597-KIT
2019 34 FIT4 Damper Shaft Assy, E-Bike Tune

820-05-538-KIT
2019 34 FIT4 F-S Topcap Assy, E-Bike Tune

038-01-073
Retaining Ring: Wire [1.280 OD X .024 CS] SS

210-22-920
Compression Adjust Coupler, F-S, FIT4

029-08-068
Seals: O-Ring [3.0MM ID x 1.5MM CS] Metric, N-70, Static

TORQUE:
55±5 IN.LB.

TORQUE:
55±5 IN.LB.

(T) Pressure Tube, 15.5 Bore, 160 Max Travel, FIT4

039-00-243
Spring: Detent [.138 TLG X .087 OD X 48 lb/in] SS

010-01-012
Air Valve Parts: Ball [Ø 0.1094] E52100 Grade 25 Steel, Chrome

GREASE:
THIN LAYER
OF SLICK HONEY ON BALL

COMPRESS DAMPER SHAFT 3IN BEFORE SEALING DAMPER

ASSEMBLE THESE PARTS AFTER OIL FILL

PROPRIETARY
THIS DOCUMENT CONTAINS CONFIDENTIAL, PROPRIETARY INFORMATION
THAT IS FOX PROPERTY. DO NOT DISCLOSE TO OR DUPLICATE
FOR OTHERS EXCEPT AS AUTHORIZED BY FOX.

FOX FOX Factory, Inc. Ph 831-768-1100
130 Hangar Way, Watsonville, CA 95076 USA Fax 831-768-9312

TITLE
**2019 34 160 MAX E-Bike &
SPD-PED F-S FIT4 Cart Assy, 3Pos-Adj**

SIZE DWG. NO.

C

PLOT SCALE | .00:1 |

SHEET | OF | 1

PrøE ASSEM

4

3

2

1