

4

3

2

1

820-05-454-KIT
2018 Grip P-S Topcap Interface Parts



TORQUE:
4±1 in-lb

039-00-375

Spring: Wave, 4 Turns, [1.562 Bpre, .375 Shaft, .260 Height, 37.0 lb/in] SS

210-24-123

Damping Adj Part: Detent, Molded, Grip

(210-24-123)

036-01-044

Seals: U-Cip, Shore 70A, 2013 CTD-ADJ, Remote O/C-CTD



GREASE:
THIN LAYER
OF SLICK HONEY

210-24-249
Damping Adj Part: Knob, Comp Selector, 34/36 Grip

2019 34 27.5, Grip E-Bike Cart Assy

820-05-328-KIT
2017 34 27.5 and 29in Grip Bottom Stud Interface Parts

241-01-011
Fastener, Custom: Crush Washer, Plastic, 13mm

241-00-011
Fastener, Custom: Nut, Bottom, R

210-03-178
Knob, Rebound, 2-Stroke, Knurled, M10 Nut



TORQUE:
5.0±0.5 IN.LB.



LOCTITE:
BLUE 242 OR 243
ONE DROP



TORQUE:
150±7
(IN-LB)

018-01-004-A
Fastener, Standard: Screw [#8-32 X 0.250 TLG]
303 SS, Socket Set Half Dog Point

REFERENCE ONLY
(FOR INSTALLATION
INTO FORK)



GREASE:
LIBERALLY WITH
SLICK HONEY

(039-00-375)

(210-24-123)

(036-01-044) NOTE ORIENTAION

(210-24-123)

ENGAGE 2X FEATURES

SECTION A-A
SCALE 2.500

PROPRIETARY
THIS DOCUMENT CONTAINS CONFIDENTIAL, PROPRIETARY INFORMATION
THAT IS FOX PROPERTY. DO NOT DISCLOSE TO OR DUPLICATE
FOR OTHERS EXCEPT AS AUTHORIZED BY FOX.

FOX **FOX Factory, Inc.** Ph 831-768-1100
130 Hangar Way, Watsonville, CA 95076 USA Fax 831-768-9312

TITLE
**2019 34 27.5 & 29, Grip
E-Bike Cart Assy Complete**

SIZE DWG. NO.
820-18-135-KIT

PLOT SCALE 0.75:1

SHEET 1 OF 2

4

3

2

Pr oE ASSEM