


- ASSEMBLY INSTRUCTIONS:
1. ASSEMBLE DAMPER SHAFT ASSEMBLY TO PRESSURE TUBE
 2. FILL CARTRIDGE 1/2 FULL WITH OIL
 3. STROKE DAMPER SHAFT 5X, THEN TOP OUT DAMPER SHAFT
 4. FILL OIL HEIGHT TO PRESSURE TUBE BLEED HOLE
 5. TOPCAP ASSY
 - A. SLOWLY PUSH INTO PRESSURE TUBE AND ENGAGE TOPCAP THREADS
 - B. ROTATE TO ENGAGE 1-2 THREADS
 6. TORQUE TOPCAP AND SEALHEAD ASSEMBLIES
 7. STROKE DAMPER SHAFT APPROXIMATELY 75% OF MAX DAMPER TRAVEL TO EXPELL EXCESS OIL



		FOX Factory, Inc.	Ph 831-768-1100
		130 Hangar Way, Watsonville, CA 95076 USA	Fax 831-768-9312
2019 36 Rhythm 180 MAX, Grip Cart Assy			
SIZE	DWG. NO.		
C			
PLOT SCALE 0.75:1		SHEET 1 OF 1	

- PROPRIETARY -
THIS DOCUMENT CONTAINS CONFIDENTIAL, PROPRIETARY INFORMATION
THAT IS FOX PROPERTY. DO NOT DISCLOSE TO OR DUPLICATE
FOR OTHERS EXCEPT AS AUTHORIZED BY FOX.